



## **Specification**

The Zurn P886-FGF Frame and Grate, Ductile Iron Frame and Grate, is 5-3/8 inches wide by 20 inches long, weighing 18.7 lbs per linear foot. The grate has an open area of 20.5 square inches per linear foot, DIN Rating of F, ANSI Rating of Special Duty, H-20 Load Rated, FAA Load Rated. Supplied by Trench Drain Supply.

GF - Duct	tile Frame & Grate
Material:	Ductile Iron
OIN Rating	: Class F
Neight:	18.7 lbs/ft.
Open Area	: 20.5 in <sup>2</sup> /ft.
ANSI Ratin	g: Special Duty
Application	: Extra-Heavy loads
Slot Width	Hole Size: 3/8"
ADA:	No
H-20:	Yes
FAA:	Yes



DISCLAIMER - The customer and the customer are architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Supply and/or its manufacturers. TRENCH DRAIN SUPPLY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTIBILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.