



## **Specification**

The Zurn P6-GDE Slotted Grate, Galvanized Ductile Iron Grate, is 5-3/8 inches wide by 20 inches long, weighing 6.4 lbs per linear foot. The grate has an open area of 27.8 square inches per linear foot, DIN Rating of E, ANSI Rating of Special Duty, H-20 Load Rated, FAA Load Rated. Galvanizing (Hot dip) conforms to ASTM specification A123. Supplied by Trench Drain Supply.

| Material: 0 | Galvanized Ductile Iron      |
|-------------|------------------------------|
| OIN Rating  | g: Class E                   |
| Weight:     | 6.4 lbs/ft.                  |
| Open Area   | a: 27.8 in <sup>2</sup> /ft. |
| ANSI Rati   | ng: Special Duty             |
| Application | n: Dynamic loads             |
| Slot Width  | n/Hole Size: 1/2"            |
| ADA:        | No                           |
| H-20:       | Yes                          |
| FAA:        | Yes                          |



DISCLAIMER - The customer and the customer are architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Supply and/or its manufacturers. TRENCH DRAIN SUPPLY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTIBILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.