



Specification

The Zurn P886-GFG-USA Frame and Grate, Galvanized Ductile Iron Frame and Grate, is 5-3/8 inches wide by 20 inches long, weighing 18.7 lbs per linear foot. The grate has an open area of 20.5 square inches per linear foot, DIN Rating of F, ANSI Rating of Special Duty, H-20 Load Rated, FAA Load Rated. Galvanizing (Hot dip) conforms to ASTM specification A123. Supplied by Trench Drain Supply.





GFG-USA -	Ductile Frame & Grate
Material: Ga	alvanized Ductile Iron
DIN Rating:	Class F
Weight:	18.7 lbs/ft.
Open Area:	20.5 in ² /ft.
ANSI Rating	g: Special Duty
Application:	Extra-Heavy loads
Slot Width/H	Hole Size: 3/8"
ADA:	No
H-20:	Yes
FAA:	Yes

DISCLAIMER - The customer and the customer are architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Supply and/or its manufacturers. TRENCH DRAIN SUPPLY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTIBILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.