1-877-903-7246



www.trenchdrainsupply.com

Number 58524	Series Z886-GHPD B Class Galvanized DI Grate P6-GHPD
20 [·	508] — <u>3</u> [19] <u>-</u>
	$5\frac{3}{58}$ [137]
by 20 inches long, weighing 6.3 lbs square inches per linear foot, DIN R	tted, Galvanized Ductile Iron Grate, is 5-3/8 inches wide per linear foot. The grate has an open area of 17.0 tating of B, ANSI Rating of Medium-Duty, ADA compliant. STM specification A123. Supplied by Trench Drain
The Zurn P6-GHPD Heel-Proof Slot by 20 inches long, weighing 6.3 lbs square inches per linear foot, DIN R Galvanizing (Hot dip) conforms to A	per linear foot. The grate has an open area of 17.0 Lating of B, ANSI Rating of Medium-Duty, ADA compliant. STM specification A123. Supplied by Trench Drain GHPD - Heel-Proof Slotted
The Zurn P6-GHPD Heel-Proof Slot by 20 inches long, weighing 6.3 lbs square inches per linear foot, DIN R Galvanizing (Hot dip) conforms to A	per linear foot. The grate has an open area of 17.0 Lating of B, ANSI Rating of Medium-Duty, ADA compliant. STM specification A123. Supplied by Trench Drain GHPD - Heel-Proof Slotted Material: Galvanized Ductile Iron
The Zurn P6-GHPD Heel-Proof Slot by 20 inches long, weighing 6.3 lbs square inches per linear foot, DIN R Galvanizing (Hot dip) conforms to A	per linear foot. The grate has an open area of 17.0 Lating of B, ANSI Rating of Medium-Duty, ADA compliant. STM specification A123. Supplied by Trench Drain GHPD - Heel-Proof Slotted Material: Galvanized Ductile Iron DIN Rating: Class B
The Zurn P6-GHPD Heel-Proof Slot by 20 inches long, weighing 6.3 lbs square inches per linear foot, DIN R Galvanizing (Hot dip) conforms to A	per linear foot. The grate has an open area of 17.0 Lating of B, ANSI Rating of Medium-Duty, ADA compliant. STM specification A123. Supplied by Trench Drain GHPD - Heel-Proof Slotted Material: Galvanized Ductile Iron DIN Rating: Class B Weight: 6.3 lbs/ft.
The Zurn P6-GHPD Heel-Proof Slot by 20 inches long, weighing 6.3 lbs square inches per linear foot, DIN R Galvanizing (Hot dip) conforms to A	per linear foot. The grate has an open area of 17.0 Lating of B, ANSI Rating of Medium-Duty, ADA compliant. STM specification A123. Supplied by Trench Drain GHPD - Heel-Proof Slotted Material: Galvanized Ductile Iron DIN Rating: Class B Weight: 6.3 lbs/ft. Open Area: 17.0 in ² /ft.
The Zurn P6-GHPD Heel-Proof Slot by 20 inches long, weighing 6.3 lbs square inches per linear foot, DIN R Galvanizing (Hot dip) conforms to A	per linear foot. The grate has an open area of 17.0 Lating of B, ANSI Rating of Medium-Duty, ADA compliant. STM specification A123. Supplied by Trench Drain GHPD - Heel-Proof Slotted Material: Galvanized Ductile Iron DIN Rating: Class B Weight: 6.3 lbs/ft. Open Area: 17.0 in ² /ft. ANSI Rating: Medium-Duty
The Zurn P6-GHPD Heel-Proof Slot by 20 inches long, weighing 6.3 lbs square inches per linear foot, DIN R Galvanizing (Hot dip) conforms to A Supply.	per linear foot. The grate has an open area of 17.0 Lating of B, ANSI Rating of Medium-Duty, ADA compliant. STM specification A123. Supplied by Trench Drain GHPD - Heel-Proof Slotted Material: Galvanized Ductile Iron DIN Rating: Class B Weight: 6.3 lbs/ft. Open Area: 17.0 in ² /ft. ANSI Rating: Medium-Duty Application: Heel-Proof
The Zurn P6-GHPD Heel-Proof Slot by 20 inches long, weighing 6.3 lbs square inches per linear foot, DIN R Galvanizing (Hot dip) conforms to A	per linear foot. The grate has an open area of 17.0 Lating of B, ANSI Rating of Medium-Duty, ADA compliant. STM specification A123. Supplied by Trench Drain GHPD - Heel-Proof Slotted Material: Galvanized Ductile Iron DIN Rating: Class B Weight: 6.3 lbs/ft. Open Area: 17.0 in ² /ft. ANSI Rating: Medium-Duty Application: Heel-Proof Slot Width/Hole Size:1/4"
The Zurn P6-GHPD Heel-Proof Slot by 20 inches long, weighing 6.3 lbs square inches per linear foot, DIN R Galvanizing (Hot dip) conforms to A Supply.	per linear foot. The grate has an open area of 17.0 Tating of B, ANSI Rating of Medium-Duty, ADA compliant. STM specification A123. Supplied by Trench Drain GHPD - Heel-Proof Slotted Material: Galvanized Ductile Iron DIN Rating: Class B Weight: 6.3 lbs/ft. Open Area: 17.0 in ² /ft. ANSI Rating: Medium-Duty Application: Heel-Proof Slot Width/Hole Size:1/4" ADA: Yes
The Zurn P6-GHPD Heel-Proof Slot by 20 inches long, weighing 6.3 lbs square inches per linear foot, DIN R Galvanizing (Hot dip) conforms to A Supply.	per linear foot. The grate has an open area of 17.0 Lating of B, ANSI Rating of Medium-Duty, ADA compliant. STM specification A123. Supplied by Trench Drain GHPD - Heel-Proof Slotted Material: Galvanized Ductile Iron DIN Rating: Class B Weight: 6.3 lbs/ft. Open Area: 17.0 in ² /ft. ANSI Rating: Medium-Duty Application: Heel-Proof Slot Width/Hole Size:1/4"

DISCLAIMER - The customer and the custom