

Number 94454	Series Z886-GHPDE  E Class Galvanized Ductile Iron Grate P6-GHPDE
ia de la companya de	$1\frac{3}{4}$ [46] $\longrightarrow$
20 [506] —	$\frac{3}{4} [19] \rightarrow$
	5 [137]
	58 [13/]   wind
C 1998 1998 C C C C C	

## **Specification**

The Zurn P6-GHPDE Heel-Proof Slotted, Galvanized Ductile Iron Grate, is 5-3/8 inches wide by 20 inches long, weighing 9.5 lbs per linear foot. The grate has an open area of 22.2 square inches per linear foot, DIN Rating of E, ANSI Rating of Special-Duty, ADA compliant, H-20 Load Rated and FAA Load Rated. Galvanizing (Hot dip) conforms to ASTM specification A123. Supplied by Trench Drain Supply.

<b>GHPDE - Hee</b>	I-Proof Slotted
Material:	Galvanized Ductile Iron
DIN Rating:	Class E
Weight:	9.5 lbs/ft.
Open Area:	22.2 in <sup>2</sup> /ft.
ANSI Rating:	Special-Duty
Application:	Heel-Proof, Forklifts, Commercial Aircraft
Slot Width/Ho	le Size: 5/16"
ADA:	Yes
H-20:	Yes
FAA:	Yes



DISCLAIMER - The customer and the customer are architects, engineers, consultants, and other professionals are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Supply and/or its manufacturers. TRENCH DRAIN SUPPLY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTIBILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.