

Number	Series Z886-HPDE
94454	E Class Heel-Proof Ductile Iron Grate P6-HPDE
ä	$1\frac{3}{4} \left[46\right] \longrightarrow$
20 [506] —	<u>₹</u> [19]
	53 [137]

Specification

The Zurn P6-HPDE Heel-Proof Slotted, Ductile Iron Grate, is 5-3/8 inches wide by 20 inches long, weighing 9.5 lbs per linear foot. The grate has an open area of 22.2 square inches per linear foot, DIN Rating of E, ANSI Rating of Special-Duty, ADA compliant, H-20 Load Rated and FAA Load Rated. Supplied by Trench Drain Supply.

HPDE - Heel-	Proof Slotted
Material:	Ductile Iron
DIN Rating:	Class E
Weight:	9.5 lbs/ft.
Open Area:	22.2 in ² /ft.
ANSI Rating:	Special-Duty
Application:	Heel-Proof, Forklifts, Commercial Aircraft
Slot Width/Ho	le Size: 5/16"
ADA:	Yes
H-20:	Yes
FAA:	Yes

Manufacturer



DISCLAIMER - The customer and the customer are completely responsible for the selection installation and maintenance of any product purchased from Trench Drain Supply and/or its manufacturers. TRENCH DRAIN SUPPLY MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY, DESIGN, MERCHANTIBILITY, OR FITNESS OF THE PRODUCT FOR CUSTOMERS APPLICATION. The drawing and information provided remain the property and copyright of the manufacturer listed. The manufacturer reserves the right to modify specification without notice.