



Channel multi V+® 100					
External width: 136mm Internal width: 100mm Length: 500mm					
Channel reference:	Height (mm)		Hydraulic section (cm ²)	Ø outlet (mm)	
	a	b		Vert	Horiz
R100F10RM/RMJ	150	112	91,5	90	75
R100F20RM/RMJ	200	162	133	90	110

Supplied By:
TRENCHDRAIN SUPPLY
 877-903-7246
 www.trenchdrainsupply.com

Review: 2017-03

ULMA Architectural Solutions reserves the right to modify the specifications of any of its products without prior notice.

Information about the shown products is only indicative and is based on the existing technical features at the time of issuing.

In the event of any discrepancy in the translation of this document into different languages, the Spanish version will be used.

Latest version in www.ulmaarchitectural.com

For more details, see technical sheets and installation guide.

Description

ULMA polymer concrete linear drainage channel model MultiV+® R100FM/RMJ. Self-cleaning optimized V-shaped V+ section.

Protective galvanized steel edge with a real thickness of 2+2 mm, smooth, without breakage of the protective zinc layer, avoiding water accumulation and preventing corrosion.

8 point bolt-locked system per lm.

Load class up to D400, EN 1433 Standard.

Grooved to ease joint sealing and vertically and horizontally channel aligning tongue and groove.

CE Conformity Declaration and compliance with EN 1433 Standard.

External width 136mm, internal width 100mm and total length 500mm. Total heights available between 150mm and 200mm. Installation possible with no slope or stepped fall.

Preformed knockouts with triple lipped seals for water tight connection (RMJ).



ARCHITECTURAL SOLUTIONS



Tel.: +34 943 78 06 00
 info@ulmaarchitectural.com
 ulmaarchitectural.com