


Z706-HDG

6 [159] WIDE REVEAL FRAME AND GRATE SYSTEM WITH GALVANIZED STEEL FRAME

TAG

Dimensional Data (inches and [mm]) are Subject to Manufacturing Tolerances and Change Without Notice

SPECIFYING ENGINEER IS RESPONSIBLE FOR CONCRETE ENCASEMENT AND REINFORCING BASED UPON APPLICATION AND LOCAL CODES



ENGINEERING SPECIFICATION: Zurn Z706-HDG

Frame and Grate System shall be 120 [3048] long, 6 [152] wide and have a 4 [102] clear opening. Frame shall mechanically lock into the concrete surround every 10 [254]. Shall be provided with standard GDC grates that lock down to frame. Zurn 6 [152] wide reveal Galvanized Ductile Iron Slotted Grate conforming to ASTM specification A536-84, Grade 80-55-06. Ductile Iron grate is rated class C per the DIN EN1433 top load classifications. Supplied in 20 [508] nominal lengths with 1/2 [13] wide slots, and 3/4 [19] bearing depth. Grate has an open area of 28.1 sq. in per ft. [59,463 sq. mm per meter]. The .105 [2.66] thick Heavy-Duty Carbon Steel Galvanized Frame Assembly conforms to ASTM specification A36 and Galvanizing conforms to ASTM specification A123 with 12 - 4 [102] long concrete anchors per 120 [3048]. Grate lockdown bars are to be integral to the frame. All welds must be performed by a certified welder per ASTM standard AWS D1.1. Frames Shall be produced in the U.S.A.

PREFIX OPTIONS (Check/specify appropriate options)

Z Ten-foot, Galvanized Heavy Duty Frame Assembly with Anchor Studs*

SUFFIX OPTIONS (Check/specify appropriate options)

Grate Options (Load Classifications are per DIN EN1433)

- -BDC Black Acid Resistant Epoxy Coated Ductile Grate Class C
- -BDE Black Acid Resistant Epoxy Coated Ductile Grate Class E
- -DC Ductile Iron Solid Cover Class C
- -DGC Ductile Iron Slotted Grate Class C
- _____ -GDC Galvanized Ductile Slotted Grate Class C *
- _____ -GDE Galvanized Ductile Slotted Grate Class E
- -GHPD Galvanized Heel-Proof Ductile Grate Class B
- -GHPDE Galvanized Heel-Proof Ductile Grate Class E
- -HPD Heel-Proof Ductile Slotted Grate Class B
- _____ -HPDE Heel-Proof Ductile Slotted Grate Class E
- -HPP Heel-Proof Polyethylene Grate Class A
- -RFG Reinforced Galvanized Steel Slotted Grate Class B
- -RPG Reinforced Galvanized Perforated Grate Class B
- -RFGC Reinforced Slotted Galvanized Grate Class C
- _____ -RPGC Reinforced Perforated Galvanized Grate Class C
- -RPGRC Reinforced Perforated Galvanized Reverse Punch Grate Class C

Miscellaneous Options

\/D	Vandal-Proof Lockdown	AWG	Aluminum Wire Grate - Class A
RC	Rebar Clip	-BDE	Black Acid Resistant Epoxy Coated Ductile Grate - Class E
RC	Rebai Cilp	-DGC-USA	Ductile Iron Slotted Grate - Class C
Decorative G	crate Options (Load Classifications are per DIN EN1/33)	DGE-USA	Ductile Iron Slotted Grate - Class E

-FG

-GDC-USA

-GDE-USA

- Decorative Grate Options (Load Classifications are per DIN EN1433) _____-BCD Bronze Circular Decorative Grate - Class A
- -BDD Bronze Diagonal Decorative Grate Class A
- -DCD Ductile Iron Circular Decorative Grate Class A
- -DDD Ductile Iron Diagonal Decorative Grate Class A
- -DOG Ductile Iron Decorative Grate Class A
- -DWV Ductile Wave Decorative Grate Class A
- -HPB Heel-Proof Bronze Slotted Grate Class A



*REGULARLY FURNISHED UNLESS OTHERWISE SPECIFIED

		Galvanized Heel-Proof Ductile Grate - Class E Heel-Proof Ductile Slotted Grate - Class E
		Plastic Perforated Grate - Class A
F	-	Perforated Galvanized Steel Grate - Class A
		n the U.S.A. (Load Classifications are per DIN EN1433)
	BZ	Bronze Decorative Grate - Class A
		Nickel Bronze Decorative Grate - Class A

Galvanized Ductile Slotted Grate - Class C

Galvanized Ductile Slotted Grate - Class E

Fabricated Galvanized Steel Slotted Grate - Class A

MADE in the U.S.A. (Load Classifications are per DIN EN1433)

PROD./DWG. NO. Z706-HDG

ZURN INDUSTRIES, LLC ♦ SPECIFICATION DRAINAGE OPERATION ♦ 1801 Pittsburgh Ave. ♦ Erie, PA 16514 Phone: 814\455-0921 ♦ Fax: 814\454-7929 ♦ World Wide Web: www.zurn.com

In Canada: ZURN INDUSTRIES LIMITED 🔶 3544 Nashua Drive 🔶 Mississauga, Ontario L4V1L2 🔶 Phone: 905/405-8272 Fax: 905/405-1292