
Supplied By: 877-903-7246 Sector S



ENGINEERING SPECIFICATION: Zurn Z806

Channels shall be 120 [3048] long, 6 [152] wide and have a 4 [102] throat. Modular channel sections shall be made of Fiber Reinforced Polymer (FRP). Shall have a positive mechanical connection between channel sections that will not separate during the installation and shall mechanically lock into the concrete surround every 10 [254]. Channels shall weigh less than 2.31 lbs.[1.05kg] per linear foot, have a smooth, 1-1/2 [38] radiused self cleaning bottom with a Manning's coefficient of .009 and .75% or neutral 0% built in slope. Shall be provided with standard DGC grates that lock down to frame. Zurn 6 [152] wide reveal Ductile Iron Slotted Grate conforming to ASTM specification A536-84, Grade 80-55-06. Ductile Iron grate is rated class C per the DIN EN1433 top load classifications. Supplied in 20 [508] nominal lengths with 1/2 [13] wide slots, and 3/4 [19] bearing depth. Grate has an open area of 18.57 sq. in per ft. [39,307 sq. mm per meter]. The 1/4 [6] thick Heavy-Duty Carbon Steel Frame Assembly conforms to ASTM specification A36 with 12-4 [102] long concrete anchors per 120 [3048]. Grate lockdown bars are to be integral to the frame. The frame is supplied with a powder coated finish. All welds must be performed by a certified welder per ASTM standard AWS D1.1. Frames Shall be provided in the U.S.A.

in the U.S.A.						_		
	ONS (Check/specify appropriate options)		Trench	'A'	'B'		Flow	
	en-foot Fiber Reinforced Polymer (FRP)*		No.	Shallow Inv.	Deep Inv.	(cfs)	(gpm)	(lps)
	en-foot Fiber Reinforced Vinylester		1001	3.50 [89]	4.40 [112]	.196	88	6
	,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,,		1001			.130	133	8
	ONS (Check/specify appropriate options)			4.40 [112]	5.30 [135]			-
Outlet Adapters Add/Each			1002N	5.30 [135]	5.30 [135]	-	-	-
-E1 Closed End Cap -U2 2 [51] No-Hub Bottom Outlet -E2 2 [51] No-Hub End Outlet -U3 3 [76] No-Hub Bottom Outlet -E3 3 [76] No-Hub End Outlet -U4 4 [102] No-Hub Bottom Outlet			1003	5.30 [135]	6.20 [157]	.397	178	11
			1004	6.20 [157]	7.10 [180]	.501	225	14
		utlet	1004N	7.10 [180]	7.10 [180]	-	-	-
	I [102] No-Hub End OutletU6 6 [152] No-Hub Bottom O [152] No-Hub End Outlet	ullet	1005	7.10 [165]	8.00 [203]	.604	271	17
			1006	8.00 [203]	8.90 [203]	.711	319	20
Frame Options			1000	8.90 [226]	9.80 [249]	.816	366	23
	Black Acid Resistant Coated Frame							-
HD	Extra-Heavy-Duty Frame Assembly with Anchor Studs *		1008	9.80 [249]	10.70 [272]	.922	414	26
Grate Ontions	(Load Classifications are per DIN EN1433)		1008N	10.70 [272]	10.70 [272]	-	-	-
-BDC	Black Acid Resistant Epoxy Coated Ductile Grate - Class C		1009	10.70 [272]	11.60 [295]	1.029	462	29
-BDE	Black Acid Resistant Epoxy Coated Ductile Grate - Class E		1010	11.60 [295]	12.50 [318]	1.136	510	32
BG	Galvanized Ductile Iron Cast Bar Grate - Class C							
DBG	Ductile Iron Cast Bar Grate - Class C	SC			cular Decorativ			
DC	Ductile Iron Solid Cover - Class C	SD			agonal Decorat		 Class 	В
DGC	Ductile Iron Slotted Grate - Class C *	SN			sh Grate - Cla			
-DGE	Ductile Iron Slotted Grate - Class E	SO	G Stai	nless Steel De	corative Grate	- Class B	5	
DGE-NA	A Ductile Iron Slotted Grate - Class E - North American							
GDC	Galvanized Ductile Slotted Grate - Class C	Miscellan						
GDE	Galvanized Ductile Slotted Grate - Class E	DB		om Dome Stra	ainer			
GG	Fiberglass Grate - Class A	JC		t Connector	0)			
	Galvanized Heel-Proof Ductile Grate - Class B			ar Clip (Set of			(D D	
	E Galvanized Heel-Proof Ductile Grate - Class E				ewall Extensio	n Adapte	r (Per Pa	air)
HPD	Heel-Proof Ductile Slotted Grate - Class B	VP	van	dal-Proof Lock	down			
HPDE	Heel-Proof Ductile Slotted Grate - Class E	MADE in t	the U.S.A	(Load Classif	ications are pe	r DIN EN	1433)	
HPP	Heel-Proof Polyethylene Grate - Class A	-AV	/G	Aluminum Wi	re Grate - Clas	ss A		
-LD	Ductile Iron Longitudinal Slotted Grate - Class B	-BD			esistant Epoxy		Ductile G	rate -
	Reinforced Galvanized Steel Slotted Grate - Class B			Class E				
	Reinforced Galvanized Perforated Grate - Class B	DC	E-USA	Ductile Iron S	Solid Cover - C	lass E		
	Reinforced Slotted Galvanized Grate - Class C		C-USA	Ductile Iron S	Slotted Grate -	Class C		
	Reinforced Slotted Stainless Steel Grate - Class C		E-USA	Ductile Iron S	Slotted Grate -	Class E		
	Reinforced Perforated Galvanized Grate - Class C	FG			alvanized Stee		Grate -	Class A
	Reinforced Galvanized Perforated Reverse Punch	FS		Fabricated St	tainless Steel S	Slotted G	rate - Cla	ass A
	Anti-Slip ADA Grate - Class C	GD	C-USA	Galvanized D	Juctile Slotted	Grate - C	lass C	
	C Reinforced Perforated Galvanized Reverse Punch Grate -Class C	GD	E-USA	Galvanized D	Ductile Slotted	Grate - C	lass E	
	Reinforced Perforated Stainless Steel Grate - Class C	G⊦	IPDE-USA	Galvanized F	leel-Proof Grat	e - Class	E	
RPSR	Reinforced Stainless Steel Perforated Reverse Punch	GN	/IG	Galvanized S	steel Mesh Gra	ite - Class	s B	
	Anti-Slip ADA Grate - Class B		DE-USA	Heel-Proof D	uctile Slotted C	Grate - Cl	ass E	
RPSRC	Reinforced Perforated Stainless Steel Reverse Punch Grate - Class C				alvanized Stee			
Descention On	-t- Onting (Land Olarsifications are public EN4 400)	PG	ίR		Perforated Rev		ch	
	ate Options (Load Classifications are per DIN EN1433)				Grate - Class /			
BCD	Bronze Circular Decorative Grate - Class A	PP			ated Grate - C			
BDD	Bronze Diagonal Decorative Grate - Class A	PS			ainless Steel G			
DCD	Ductile Iron Circular Decorative Grate - Class C	PS	R	Stainless Ste	el Perforated	Reverse	Punch A	nti-Slip
DDD	Ductile Iron Diagonal Decorative Grate - Class A			Grate - Class				
DOG	Ductile Iron Decorative Grate - Class A	Decorative	e MADE i	n the U.S.A. (Load Classifica	ations are	per DIN	EN143
DTW	Ductile Iron Tidal Wave Grate - Class C	BZ		Bronze Deco	rative Grate - C	Class A		
DWV	Ductile Wave Decorative Grate - Class A	NB			e Decorative G			
HPB	Heel-Proof Bronze Slotted Grate - Class A		E-USA		Perforated ADA			
HPS	Heel-Proof Stainless Steel Slotted Grate - Class A	PS	R		el Perforated I	Reverse I	Punch	
SBG	Stainless Steel Bar Grate - Class E			Anti-Slip Grat				
* Regularly fur	rnished unless otherwise specified.	SV	/G	Stainless Stee	el Wire Grate -	· Class A		
	s, LLC Specification Drainage Operation Avenue Frie PA USA 16502 Ph 855-663-9876 Fax 814-454-7929		Rev.	AD				

1801 Pittsburgh Avenue, Erie, PA U.S.A. 16502 · Ph. 855-663-9876, Fax 814-454-7929

In Canada | Zurn Industries Limited 3544 Nashua Drive, Mississauga, Ontario L4V 1L2 · Ph. 905-405-8272, Fax 905-405-1292

www.zurn.com

Date: 07/18/14 C.N. No. 131244 Prod. | Dwg. No. Z806