CDE	> A T	CHEET
SPE	 . 411	SHEET

TAG

Dimensional Data (inches and [mm]) are Subject to Manufacturing Tolerances and Change Without Notice

SPECIFYING ENGINEER IS RESPONSIBLE FOR CONCRETE ENCASEMENT AND REINFORCING BASED UPON APPLICATION AND LOCAL CODES [151] [1048] 102 | MIN 102] MIN NOTE: + Actual Channel length is $41\frac{1}{4}$ [1048] to allow for overlap.

ENGINEERING SPECIFICATION: Zurn Z883

Channels shall be 40" [1016mm] long, 6" [152mm] wide reveal and have a 4" [102mm] throat. Modular channel sections shall be made of 0% water absorbent Polypropylene. Shall have a positive mechanical connection between channel sections that will not separate during the installation and shall mechanically lock into the concrete surround a minimum of every 10" [254mm]. Channels shall weigh less than 2.31 lbs.[1.05kg] per linear foot, have a smooth, 2" [51mm] radiused self cleaning bottom with a Manning's coefficient of .009 and neutral 0% built in slope. Channels shall have rebar clips standard to secure trench in its final location. Shall be provided with standard DGC grates that lock down with lockdown bars to the channel and is not intended for dynamic traffic loadings. Zurn 5.375" [137mm] wide reveal Ductile Iron Slotted Grate conforming to ASTM specification A536-84, Grade 80-55-06. Ductile Iron grate is rated class C per the DIN EN1433 top load classifications. Supplied in 20" [508mm] nominal lengths with .50" [13mm] wide slots, and .75" [19mm] bearing depth. Grate has an open area of 28.1 sq. in per ft. [59,463 sq. mm per meter].

PREFIX OPTIONS (Check/specify appropriate options)
___ Z Three-foot, Four-inch High Density Polyethylene (HDPE)*

SUFFIX OPTIONS (Check/specify appropriate options)

Outlet Adapters Add/Each

-E1 Closed End Cap -E2 2 [51] No-Hub End Outlet

ota Ontiana (Load Classifications are nor DIN EN1422)

Grate Option	s (Load Classifications are per DIN EN1433)		
BDC	Black Acid Resistant Epoxy Coated Ductile Grate - Class C	Decorative G	Grate Options (Load Classifications are per DIN EN1433)
BG	Galvanized Ductile Iron Bar Grate - Class C	BCD	Bronze Circular Decorative Grate - Class A
DBG	Ductile Iron Cast Bar Grate - Class C	BDD	Bronze Diagonal Decorative Grate - Class A
DC	Ductile Iron Solid Cover - Class C	DCD	Ductile Iron Circular Decorative Grate - Class C
-DGC	Ductile Iron Slotted Grate - Class C *	DDD	Ductile Iron Diagonal Decorative Grate - Class A
GDC	Galvanized Ductile Slotted Grate - Class C	DOG	Ductile Iron Decorative Grate - Class A
GG	Fiberglass Grate - Class A	DWV	
GHPD	Galvanized Heel-Proof Ductile Grate - Class B	GMG HPB	Galvanized Steel Mesh Grate - Class A Heel-Proof Bronze Slotted Grate - Class A
HPD	Heel-Proof Ductile Slotted Grate - Class B	HPS	Heel-Proof Stainless Steel Slotted Grate - Class A
HPP	Heel-Proof Polyethylene Grate - Class A	-SBG	Stainless Steel Bar Grate - Class B
RFG	Reinforced Galvanized Steel Slotted Grate - Class B	-SCD	Stainless Steel Circular Decorative Grate - Class B
RFS	Reinforced Stainless Steel Slotted Grate - Class B	SDD	Stainless Steel Diagonal Decorative Grate - Class B
RPG	Reinforced Galvanized Perforated Grate - Class B	SMG	Stainless Steel Steel Mesh Grate - Class A
-RPS	Reinforced Stainless Steel Perforated Grate - Class B	SOG	Stainless Steel Decorative Grate - Class B
NF3	Neillioided Stailliess Steel i ellolated Glate - Class B		

Miscellaneous Options							
VP Vandal-Proof Lockdown							
MADE in the U.S.	A. (Load Classifications are per DIN EN1433)	Decorative MADE	in the U.S.A. (Load Classifications are per DIN EN1433)				
AWG	Aluminum Wire Grate - Class A	BZ	Bronze Decorative Grate - Class A				
	Ductile Iron Slotted Grate - Class C	NBZ	Nickel Bronze Decorative Grate - Class A				
-FG	Fabricated Galvanized Steel Slotted Grate - Class A	-PSR	Perforated Stainless Steel Raised Grate - Class A				
-FG -FS	Fabricated Stainless Steel Slotted Grate - Class A	-SWG	Stainless Steel Wire Grate - Class A				
-GDC-USA	Galvanized Ductile Slotted Grate - Class C						
GG	Fiberglass Grate - Class A						
PG	Perforated Galvanized Steel Grate - Class A		Supplied By:				
PPC	Plastic PerforatedGrate - Class C						

Miscellaneous Options

Bottom Dome Strainer _ -DB

* Regularly furnished unless otherwise specified.

www.trenchdrainsupply.com

877-903-7246

Zurn Industries, LLC | Specification Drainage Operation 1801 Pittsburgh Avenue, Erie, PA U.S.A. 16502 Ph. 855-663-9876, Fax 814-454-7929

In Canada | Zurn Industries Limited

Perforated Stainless Steel Grate - Class A

3544 Nashua Drive, Mississauga, Ontario L4V 1L2 · Ph. 905-405-8272, Fax 905-405-1292

Rev.

Date: 03/17/15 C.N. No. 132365 Prod. | Dwg. No. Z883