

ENGINEERING SPECIFICATION

Zurn Z-888-18-DYN-HP 13" wide 1 3/4" slotted High Capacity trench drain system with Heelproof Ductile Iron Top. Heelproof top has 1/4" wide longitudinal slots. Linear low density polyethylene modular drain channel with smooth non-stick, non-corrosive interior and 0% water absorption. 80" modular sections with integral frame, mechanically interlocking joints and smooth radiused interior. Integral tie-down/leveling devices at 20" intervals, U-shaped tensile strength rebar (#4) at 10" intervals, 4,000 psi concrete encasement, and load distribution rebar stances with continuous lengths of rebar (#4) for structural integrity. (**Rebar, wire, and 4,000 psi concrete to be supplied by other.**)

CP SUFFIX OPTION ENGINEERING SPECIFICATION

Zurn Z-888-18-DYN-CP 8" wide linear low density polyethylene cleanout port. 24" long modular cleanout port with Welded Steel top frame assembly, mechanically interlocking joints, integral rebar clips and smooth radiused interior. Furnished with 8" special duty, Dura-Coated ductile iron grate and lockdown hardware, unless otherwise specified.

PREFIX OPTIONS

Z*- 80" linear low density polyethylene modular drain channel with integral top frame.

SUFFIX OPTIONS

СР	Cleanout Port with Ductile Iron Grate	
CF	Carbon Steel Dura Coated Frame Assembly with Anchor Studs	
CGF	Galvanized Carbon Steel Frame Assembly with Anchor Studs	
DF	Ductile Iron Black Dura Coated Frame	Supplied By:
DGF	Ductile Iron Galvanized Frame	TRENCHDRAIN
E1	Closed End Cap	SUPPLY
E8	8" No Hub End Outlet	877-903-7246
E12	12" No Hub End Outlet	
SF	Stainless Steel Frame Ass'y with Anchor Studs	www.trenchdrainsupply.com

*Regularly Furnished Unless Otherwise Specified

DWG. NO. 64123 PRODUCT NO. Z-888-18-HP-DYN

C.N. NO. 87928

DATE: 8/9/01

REV.